

BH SERIES PERISTALTIC PUMPS

The BH Series peristaltic pump has a constant flow rate, available in 22 l/h, 30 l/h, 40 l/h, 65 l/h and 100 l/h with Santoprene® and silicone tubing. The tube is fixed to the external fitting with SS clamps. The cover is fixed on the casing with 3 screws.



Type	Flow Rate / Pressure		Weight Kg	Power Supply Volt	Power Consumption watts	Rotation Speed 1' - rpm	Tube Size mm
	l / h	Bar					
BH - 22	22	1	1.5	220 / 240 v 50-60 Hz	40	50	8.0 x 12.8
BH - 30	30	1	1.5		40	50	9.6 x 14.4
BH - 40	40	1	1.5		40	70	
BH - 65	65	1	2.1		60	105	
BH - 100	100	1	2.1		60	150	

Circulation values refer to water, at room temperature, with a back pressure of 1 bar and a suction head of 1.5 m. Flow rate at 60 Hz increases by 20%.

MATERIALS IN CONTACT WITH THE CHEMICAL DOSES

Tubing: Santoprene® and Silicone
Fittings: Polypropylene

PUMP KIT

Our peristaltic pumps can be supplied upon request with:

Suction / discharge tube in flexible PVC
Injection valve
Foot filter

OVERALL DIMENSIONS

